

AUXILIARY COOLING AND POWER SYSTEM

Model 705899



Product description

Parker Meggitt Defense Systems is pleased to present an auxiliary cooling and power solution for land based fighting vehicles. The Auxiliary Cooling and Power System (ACPS) is designed to thrive in modern combat environments. Designed to provide cooling for crew comfort and electronic packages in addition to auxiliary power, the ACPS is a rugged, self-contained system ready for today's modern fighting vehicles. The ACPS consists of three major components, the Auxiliary Cooling and Power Unit (ACPU), the Air Handling Unit (AHU), and an Operator Panel.

The ACPU is a rugged self-contained cooling and power unit that is located on the exterior of the vehicle. On the M1 Abrams, the ACPU is mounted on the turret bustle rack. The unit contains a refrigerant based liquid cooling system and 28 VDC power generation system driven by a heavy-fuel based engine. The engine may be powered by different fuels including diesel and JP-8. The cooling system provides the AHU with cold fluid and may be used to cool electronic chassis boxes. The 28 VDC generating system is self-regulating and can be accessed via standard NATO slave plug on the interface panel on the front of the unit.

The AHU consists of a 28 VDC electrically driven fan and liquid-to-air heat exchanger. The AHU is based on the AHU used on the Thermal Management System (TMS™) for M1A2 SEP Abrams Main Battle Tank. The AHU provides conditioned air to crew as well as electronics inside the vehicle.

The Operator Panel provides a remote start and controls for the ACPS. In addition, the Operator Panel provides basic information to the operator, such as modes and faults. The unit may be started via the Operator Panel which would be located inside the vehicle near the AHU. The AHU fan speed is controlled via speed selector knob.

The ACPS takes advantage of Parker Meggitt Defense Systems extensive experience in analyzing, designing, and production of environmental control products for modern warfighting vehicles. Components selected for the ACPS are battle tested. The ACPS prototype is currently configured for the M1 tank. The ACPS may be reconfigured to meet the requirements of other fighting vehicles as well.

Key features and benefits

- Powered by Diesel and JP8
- Provides cooling and power
- Provides 6 hours of cooling without refueling
- Provides 7 kW+ of cooling and 28 VDC power
- Turret mounted Air Handling Unit (AHU)
- Closed loop R134a refrigerant
- Self sufficient system. Does not require input from vehicle to operate

Applications

- M1 Abrams Tank
- Fighting Vehicles



Parker Meggitt Defense Systems
9801 Muirlands Blvd.
Irvine, CA 92618
+1 (949) 465 7700
www.meggittdefense.com

AUXILIARY COOLING AND POWER SYSTEM

Model 705899

Specifications	
Cooling capacity Rated ambient air temperature Average air return temperature Average air delivery temperature	48.8°C (120°F) 34°C (93°F) 20.5°C (69°F) 7.0 kW+ (23,900 BTU/hr+)
Export power available When cooling system on When cooling system off Power	2.8 kW+ 7.0 kW+ 28 VDC
ACPU Fuel type Maximum fuel consumption Overall dimensions Weight	JP-8 and Diesel 3.52 kg/hr (1.2 gal/hr) 24"(61 cm) T x 25.5"(65 cm) W x 44.5"(113 cm) L 302 kg/665 lbs
Air Handling Unit Air flow Coolant type Overall dimensions Weight	400 LPS (842 CFM) maximum PGW or EGW 15.6"(40 cm) T x 17.5"(44.5 cm) W x 15"(38.5cm) L 16 kg/35 lbs
Operator Panel Overall dimensions Weight	7" (17.8cm) T x 11"(28 cm) W x 4.5"(11.5cm) L 3.6 kg/8 lbs
Standard NATO slave plug	
Provides own power for starter	
Control box provided	

Based on the M1A2 Main Battle Tank SEP Thermal Management Unit (TMS™) using many of the same refrigeration components. Heavy Fuel engine is a proven military variant of a Commercial Off the Shelf (COTS) engine. Alternator is a military model used in military vehicles. Coolant is used as medium of heat transfer between the ACPU and the AHU (in the turret). This prevents refrigerant from leaking in the vehicle. AHU uses power from ACPU. The system does not draw additional power from the vehicle. System is self-contained and self-sufficient, only requiring fuel and minor routine maintenance.



Auxiliary Cooling and Power System

